

AMENDMENTS TO THE CLAIMS

- 1 1. (Original) A method for rule-based network management, the method comprising the
2 computer-implemented steps of:
3 defining and storing a set of rules in one or more Rule-Based Markup Language
4 (“RBML”) documents, wherein the one or more RBML documents include one or
5 more tags defining one or more rule elements, and wherein the set of rules
6 includes:
7 a symptom-event rule that identifies as a symptom a particular event occurring
8 within the network; and
9 a problem-diagnosis rule that defines a problem within the network as a
10 correlation between one or more symptoms;
11 collecting and storing symptom-related data about one or more symptoms, wherein
12 collecting and storing the symptom-related data includes monitoring the network
13 for one or more network events identified in the symptom-event rule; and
14 detecting a problem within the network, wherein detecting the problem includes applying
15 the problem-diagnosis rule to the symptom-related data.
- 1 2. (Original) A method as recited in Claim 1, the method further comprising reviewing the
2 set of rules to identify and resolve a conflict between two or more rules in the set.
- 1 3. (Original) A method as recited in Claim 1, the method further comprising storing the one
2 or more RBML documents in a rule repository, wherein the rule repository includes one or more
3 directories containing RBML documents.
- 1 4. (Original) A method as recited in Claim 1, wherein a RBML document storing the
2 problem-diagnosis rule includes:
3 a problem-definition tag describing a problem; and

4 a correlation tag identifying the correlation between one or more symptoms, wherein the
5 one or more symptoms are defined in one or more symptom tags that include one
6 or more pre-defined indicators associated with the one or more symptoms.

1 5. (Original) A method as recited in Claim 4, wherein the step of detecting a problem within
2 the network further comprises the steps of:
3 comparing the symptom-related data to the one or more pre-defined indicators associated
4 with a particular symptom to determine whether the particular symptom exists in
5 the symptom-related data;
6 repeating the step of comparing the symptom-related data for all symptoms identified in
7 the correlation tag of the RBML document storing the problem-diagnosis rule;
8 and
9 only if all symptoms identified in the correlation tag exist, determining that the problem
10 identified in the problem-definition tag is detected.

1 6. (Original) A method as recited in Claim 1, wherein a RBML document storing the
2 symptom-event rule includes:
3 an event tag identifying the particular event occurring on the network; and
4 a symptom tag identifying a symptom as a generalized abstraction of the particular event.

1 7. (Original) A method as recited in Claim 6, wherein the RBML document storing the
2 symptom-event rule further includes:
3 a profile tag identifying a particular network device; and
4 a command tag identifying a data-collection command, wherein the data-collection
5 command, when executed on the particular network device, returns symptom-
6 related data associated with the particular network device.

1 8. (Original) A method as recited in Claim 1, wherein:
2 the set of rules further includes a problem-correction rule defining one or more corrective
3 actions capable of correcting the problem within the network; and

the method further comprises the step of recommending to a user one or more corrective actions defined in a RBML document storing the problem-correction rule.

9. (Original) A method as recited in Claim 8, the method further comprising the step of applying to a network device, without user intervention, one or more corrective actions defined in the problem-correction rule.

10. (Original) A method as recited in Claim 1, wherein:
the network is a first network in a plurality of networks; and
the method further comprises the steps of:
receiving a request from a user to employ a particular rule in managing a second network, separate from the first network; and
distributing to a device on the second network the one or more RBML documents storing the particular rule.

11. (Original) A method for defining a Rule-Based Markup Language (“RBML”) to describe a set of rules for managing a network, the method comprising the computer-implemented steps of:

creating one or more RBML documents for storing the set of rules, wherein the one or more RBML documents include one or more tags defining one or more rule elements, and wherein:

a RBML document storing a symptom-event rule from the set of rules includes:
an event tag identifying a particular event occurring on the network; and
a symptom tag identifying a symptom as a generalized abstraction of the particular event; and

a RBML document storing a problem-diagnosis rule from the set of rules includes:

a problem-definition tag describing a problem; and
a correlation tag identifying a correlation between one or more symptoms, wherein the one or more symptoms are defined in one or more symptom tags that include one or more pre-defined indicators associated with the one or more symptoms; and

18 generating, from information stored in one or more tags of the one or more RBML
19 documents, one or more sequences of instructions, which instructions, when
20 executed by one or more processors, cause the one or more processors to carry out
21 the steps of:
22 collecting and storing symptom-related data about one or more symptoms,
23 wherein collecting and storing the symptom-related data includes
24 monitoring the network for one or more network events identified in the
25 symptom-event rule; and
26 detecting a problem within the network, wherein detecting the problem includes
27 applying the problem-diagnosis rule to the symptom-related data.

1 12. (Original) A method as recited in Claim 11, wherein the step of detecting a problem
2 within the network further comprises the steps of:
3 comparing the symptom-related data to the one or more pre-defined indicators associated
4 with the one or more symptoms to determine whether a particular symptom exists
5 in the symptom-related data;
6 repeating the step of comparing the symptom-related data for all symptoms identified in
7 the correlation tag of the RBML document storing the problem-diagnosis rule;
8 and
9 only if all symptoms identified in the correlation tag exist, determining that the problem
10 identified in the problem-definition tag is detected.

1 13. (Original) A method as recited in Claim 11, wherein the RBML document storing the
2 symptom-event rule further includes:
3 a profile tag identifying a particular network device; and
4 a command tag identifying a data-collection command, wherein the data-collection
5 command, when executed on the particular network device, returns symptom-
6 related data associated with the particular network device.

1 14. (Original) A method as recited in Claim 11, wherein:

2 the step of creating one or more RBML documents further includes creating a RBML
3 document for storing a problem-correction rule defining one or more corrective
4 actions capable of correcting the problem within the network; and
5 the step of generating instructions includes generating one or more sequences of
6 instructions, which instructions, when executed by the one or more processors,
7 cause the one or more processors to carry out the step of recommending to a user
8 the one or more corrective actions defined in the RBML document storing the
9 problem-correction rule.

- 1 15. (Original) An apparatus for rule-based network management, comprising:
2 a rule editor for creating and storing, in one or more Rule-Based Markup Language
3 (“RBML”) documents containing one or more tags, a set of rules employed in
4 managing the network, wherein the set of rules includes:
5 a symptom-event rule that identifies as a symptom a particular event occurring
6 within the network; and
7 a problem-diagnosis rule that defines a problem within the network as a
8 correlation between one or more symptoms;
9 one or more processors;
10 a diagnosis engine including one or more stored sequences of instructions which, when
11 executed by the one or more processors, cause the one or more processors to carry
12 out the steps of:
13 collecting and storing symptom-related data about one or more symptoms,
14 wherein collecting and storing the symptom-related data includes
15 monitoring the network for one or more network events identified in the
16 symptom-event rule; and
17 detecting a problem within the network, wherein detecting the problem includes
18 applying the problem-diagnosis rule to the symptom-related data.

- 1 16. (Original) An apparatus as recited in Claim 15, wherein the rule editor is capable of
2 providing to a user means for reviewing the set of rules to identify and resolve a conflict between
3 two or more rules in the set.

1 17. (Original) An apparatus as recited in Claim 15, wherein:
2 the problem-diagnosis rule defining the correlation between one or more symptoms
3 includes one or more pre-defined indicators associated with the one or more
4 symptoms; and
5 the diagnosis engine instructions for carrying out the step of detecting a problem within
6 the network further include instructions for carrying out the steps of:
7 comparing the symptom-related data to the one or more pre-defined indicators
8 associated with the one or more symptoms to determine whether a
9 particular symptom exists in the symptom-related data;
10 repeating the step of comparing the symptom-related data for all symptoms
11 identified in the problem-diagnosis rule; and
12 only if all correlated symptoms identified in the problem-diagnosis rule exist,
13 determining that the problem defined in the problem-diagnosis rule is
14 detected.

1 18. (Original) An apparatus as recited in Claim 15, wherein the symptom-event rule further
2 includes:
3 information identifying a particular network device; and
4 a data-collection command, wherein the data-collection command, when executed on the
5 particular network device, returns symptom-related data associated with the
6 particular network device.

1 19. (Original) An apparatus as recited in Claim 15, wherein:
2 the set of rules further includes a problem-correction rule defining one or more corrective
3 actions capable of correcting the problem within the network; and
4 the diagnosis engine further includes instructions which, when executed by the one or
5 more processors, cause the one or more processors to carry out the step of
6 recommending to a user one or more corrective actions defined in the problem-
7 correction rule.

20. (Original) An apparatus as recited in Claim 19, wherein the diagnosis engine further includes instructions which, when executed by the one or more processors, cause the one or more processors to carry out the step of applying to a network device, without user intervention, one or more corrective actions defined in the problem-correction rule.

21. (Original) An apparatus as recited in Claim 19, wherein:
the network is a first network in a plurality of networks; and
the apparatus further includes a rule broker, wherein the rule broker receives a request from a user to apply a particular rule in managing a second network, separate from the first network, and distributes to a device on the second network the one or more RBML documents storing the particular rule.

22. (Currently Amended) A computer-readable storage medium carrying one or more sequences of instructions for rule-based network management, which instructions, when executed by one or more processors, cause the one or more processors to carry out the steps of:
defining and storing a set of rules in one or more Rule-Based Markup Language (“RBML”) documents, wherein the one or more RBML documents include one or more tags defining one or more rule elements, and wherein the set of rules includes:
a symptom-event rule that identifies as a symptom a particular event occurring within the network; and
a problem-diagnosis rule that defines a problem within the network as a correlation between one or more symptoms;
collecting and storing symptom-related data about one or more symptoms, wherein collecting and storing the symptom-related data includes monitoring the network for one or more network events identified in the symptom-event rule; and
detecting a problem within the network, wherein detecting the problem includes applying the problem-diagnosis rule to the symptom-related data.

- 1 23. (Currently Amended) A computer-readable storage medium as recited in Claim 22,
2 further comprising instructions which, when executed by the one or more processors,
3 cause the one or more processors to carry out the step of reviewing the set of rules to
4 identify and resolve a conflict between two or more rules in the set.
- 1 24. (Currently Amended) A computer-readable storage medium as recited in Claim 22,
2 further comprising instructions which, when executed by the one or more processors,
3 cause the one or more processors to carry out the step of storing the one or more RBML
4 documents in a rule repository, wherein the rule repository includes one or more
5 directories containing RBML documents.
- 1 25. (Currently Amended) A computer-readable storage medium as recited in Claim 22,
2 wherein a RBML document storing the problem-diagnosis rule includes:
3 a problem-definition tag describing a problem; and
4 a correlation tag identifying the correlation between one or more symptoms, wherein the
5 one or more symptoms are defined in one or more symptom tags that include one
6 or more pre-defined indicators associated with the one or more symptoms.
- 1 26. (Currently Amended) A computer-readable storage medium as recited in Claim 25,
2 further comprising instructions which, when executed by the one or more processors,
3 cause the one or more processors to carry out the steps of:
4 comparing the symptom-related data to the one or more pre-defined indicators associated
5 with a particular symptom to determine whether the particular symptom exists in
6 the symptom-related data;
7 repeating the step of comparing the symptom-related data for all symptoms identified in
8 the correlation tag of the RBML document storing the problem-diagnosis rule;
9 and
10 only if all symptoms identified in the correlation tag exist, determining that the problem
11 identified in the problem-definition tag is detected.

1 27. (Currently Amended) A computer-readable storage medium as recited in Claim 22,
2 wherein a RBML document storing the symptom-event rule includes:
3 an event tag identifying the particular event occurring on the network; and
4 a symptom tag identifying a symptom as a generalized abstraction of the particular event.

1 28. (Currently Amended) A computer-readable storage medium as recited in Claim 27,
2 wherein the RBML document storing the symptom-event rule further includes:
3 a profile tag identifying a particular network device; and
4 a command tag identifying a data-collection command, wherein the data-collection
5 command, when executed on the particular network device, returns symptom-
6 related data associated with the particular network device.

1 29. (Currently Amended) A computer-readable storage medium as recited in Claim 22,
2 wherein:
3 the set of rules further includes a problem-correction rule defining one or more corrective
4 actions capable of correcting the problem within the network; and
5 the computer-readable medium further comprises instructions which, when executed by
6 the one or more processors, cause the one or more processors to carry out the step
7 of recommending to a user one or more corrective actions defined in a RBML
8 document storing the problem-correction rule.

1 30. (Currently Amended) A computer-readable storage medium as recited in Claim 29,
2 further comprising instructions which, when executed by the one or more processors,
3 cause the one or more processors to carry out the step of applying to a network device,
4 without user intervention, one or more corrective actions defined in the problem-
5 correction rule.

1 31. (Currently Amended) A computer-readable storage medium as recited in Claim 22,
2 wherein:
3 the network is a first network in a plurality of networks; and

the computer-readable medium further comprises instructions which, when executed by the one or more processors, cause the one or more processors to carry out the steps of:
receiving a request from a user to employ a particular rule in managing a second network, separate from the first network; and
distributing to a device on the second network the one or more RBML documents storing the particular rule.

32. (Currently Amended) A computer-readable storage medium carrying one or more sequences of instructions for defining a Rule-Based Markup Language (“RBML”) to describe a set of rules for managing a network, which instructions, when executed by one or more processors, cause the one or more processors to carry out the steps of:
creating one or more RBML documents for storing the set of rules, wherein the one or more RBML documents include one or more tags defining one or more rule elements, and wherein:
a RBML document storing a symptom-event rule from the set of rules includes:
an event tag identifying a particular event occurring on the network; and
a symptom tag identifying a symptom as a generalized abstraction of the particular event; and
a RBML document storing a problem-diagnosis rule from the set of rules includes:
a problem-definition tag describing a problem; and
a correlation tag identifying a correlation between one or more symptoms, wherein the one or more symptoms are defined in one or more symptom tags that include one or more pre-defined indicators associated with the one or more symptoms; and
generating, from information stored in one or more tags of the one or more RBML documents, one or more sequences of instructions, which instructions, when executed by one or more processors, cause the one or more processors to carry out the steps of:
collecting and storing symptom-related data about one or more symptoms, wherein collecting and storing the symptom-related data includes

25 monitoring the network for one or more network events identified in the
26 symptom-event rule; and
27 detecting a problem within the network, wherein detecting the problem includes
28 applying the problem-diagnosis rule to the symptom-related data.

1 33. (Currently Amended) A computer-readable storage medium as recited in Claim 32,
2 wherein the instructions for detecting a problem within the network further comprise
3 instructions for carrying out the steps of:
4 comparing the symptom-related data to the one or more pre-defined indicators associated
5 with the one or more symptoms to determine whether a particular symptom exists
6 in the symptom-related data;
7 repeating the step of comparing the symptom-related data for all symptoms identified in
8 the correlation tag of the RBML document storing the problem-diagnosis rule;
9 and
10 only if all symptoms identified in the correlation tag exist, determining that the problem
11 identified in the problem-definition tag is detected.

1 34. (Currently Amended) A computer-readable storage medium as recited in Claim 32,
2 wherein the RBML document storing the symptom-event rule further includes:
3 a profile tag identifying a particular network device; and
4 a command tag identifying a data-collection command, wherein the data-collection
5 command, when executed on the particular network device, returns symptom-
6 related data associated with the particular network device.

1 35. (Currently Amended) A computer-readable storage medium as recited in Claim 32,
2 wherein:
3 the instructions for creating one or more RBML documents further comprise instructions
4 for carrying out the step of creating a RBML document for storing a problem-
5 correction rule defining one or more corrective actions capable of correcting the
6 problem within the network; and
7 the instructions for generating one or more sequences of instructions, by using
8 information stored in one or more tags of one or more RBML documents, further

9 comprise instructions for carrying out the step of recommending to a user the one
10 or more corrective actions defined in the RBML document storing the problem-
11 correction rule.